REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY *(Leave blank)*	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	APRIL 2002	TECHNICAL NOTE

4. TITLE AND SUBTITLE
SIMULATION OF THERMAL EFFECTS OF MICROWAVE RADIATION ON WARFIGHTERS

5. FUNDING NUMBERS

6. AUTHOR(S)

LARRY G. BERGLUND

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

U.S. Army Research Institute of Environmental Medicine
Kansas Street
Natick, MA 01760-50076

8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)
U.S. Army Medical Research and Materiel Command
Fort Detrick, MD 21702-5007

20020513 067

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION / AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

12b. DISTRIBUTION CODE

13. ABSTRACT *(Maximum 200 words)*

A thermal physiological computer model constructed using MathLab Simulink was adapted to predict the human thermal response to microwave beam radiation. The model simulates soldiers' responses to radio frequency radiation (RFR) from radar, communication and other sources. The model is operational but not complete or completely tested. The model's predictions include core and skin temperatures, skin blood flows, sweat rates, skin moisture, thermal sensation and discomfort. Simulations with the model were compared to human responses measured at Brooks Air Force Base and J.B. Pierce Laboratory from exposures to 100 and 450 MHz RFR beamed at their backs back while seated and wearing shorts. RFR intensities were 8 to 24 mw/cm^2 in environments of 28 and 31C. For this frequency range the model assumes the core absorbs the RFR energy. The agreement between model and data was fairly good. It is recommended that this development work continue with comparison testing to human response data measured at higher frequencies. Human simulation capabilities that include thermal effects of microwave radiation could facilitate planning for complex and changing activities and equipment of the modern warfighter.

14. SUBJECT TERMS	15. NUMBER OF PAGES
human simulation, thermal-physiological response, comfort response, radio frequency radiation	
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASS	UNCLASS	UNCLASS	U

USARIEM TECHNICAL REPORT T00-##

SIMULATION OF THERMAL EFFECTS OF MICROWAVE RADIATION ON WARFIGHTERS

Larry G. Berglund

Biophysics and Biomedical Modeling Division

April 2002

U.S. Army Research Institute of Environmental Medicine
Natick, MA 01760-5007

TABLE OF CONTENTS

Section — Page

List of Figures iv

Acknowledgments v

Executive Summary 1

Introduction 2
- Project objective 2
- Background 2

Methods 2
- Simulation model with microwave energy absorption 3
- Thermal sensation 3

Results 4
- Model testing 4
  - 100 MHz 5
  - 450 MHz 8

Conclusions 10

Recommendations 11

References 12

Appendix A 13

Appendix B 14

LIST OF FIGURES

Figure		Page
1	Three-compartment thermo-physiological model for microwave beam radiation	4
2	Thermal responses to100 MHz RFR in a 31C environment	5
3	Local sweat rates in a 31C environment with 100 MHz RFR	6
4	Local skin blood flow in a 31C environment with100 MHz RFR	6
5	Predicted skin moisture in a 31C environment with 100 MHz RFR	7
6	Comfort responses in a 31C environment with 100 MHz RFR	7
7	Skin and core temperatures in a 28C environment with 450 MHz RFR	8
8	Local sweat rates in a 28C environment with 450 MHz RFR	8
9	Comparison of comfort sensations with 450MHz RFR in 28C air	9
10	Comfort sensations from one subject receiving 450 MHz RFR in 31C air compared to predicted sensations	10

ACKNOWLEDGMENTS

The response data from human exposure to low and intermediate levels of 450 and 100 MHz microwave radiation measured by Dr. Eleanor Adair at Brooks Air Force Base and J.B. Pierce Laboratory is very much appreciated. The excellent data, which contains physiological and subjective responses, is particularly well suited for comparison to the predicted responses made by the simulation model, further it is likely the only such data in existence anywhere. The authors also thank Dr. Adair for sharing her insights and wisdom about thermal responses to microwaves acquired from extensive experimental observations.

EXECUTIVE SUMMARY

A thermal physiological computer model constructed using MathLab Simulink was adapted to predict the human thermal response to microwave beam radiation. The model simulates soldiers' responses to radio frequency radiation (RFR) from radar, communication and other sources. The model is operational but not complete or completely tested. The model's predictions include core and skin temperatures, skin blood flows, sweat rates, skin moisture, thermal sensation and discomfort.

Simulations with the model were compared to human responses measured at Brooks Air Force Base and J.B. Pierce Laboratory from exposures to 100 and 450 MHz RFR beamed at their back while seated and wearing shorts. RFR intensities were 8 to 24 mw/cm^2 in environments of 28 and 31C. For this frequency range the model assumes the core absorbs the RFR energy. The agreement between model and data was fairly good.

It is recommended that this development work continue with comparison testing to human response data measured at higher frequencies. Human simulation capabilities that include thermal effects of microwave radiation could facilitate planning for complex and changing activities and equipment of the modern warfighter.

INTRODUCTION

Project Objective: Develop a thermal physiological model using MathWorks Simulink to predict the human thermal response to low and moderate intensity microwave exposure.

Background

The energy exchange between a soldier and the environment is important to his or her energy balance and body temperature regulation. It affects comfort, well-being, physiological health, performance and endurance. The energy flows depend on a number of parameters of the environment and the individual, for example: air temperature, thermal radiation, wind, humidity, clothing insulation and metabolic energy production. Radio or microwaves from antennae, communication equipment, industrial machines and other devices are becoming another source of thermal energy in the environment.

Human thermal response to the environment without microwave radiation can be simulated with accuracy by various computer modeling programs at USARIEM. These physiological and environmental models are increasing accepted and used to plan and ensure soldier health and effectiveness in increasingly complex and demanding tasks. Current (USARIEM) models do not have the capability to include microwave or radio frequency radiation (RFR) in their simulations. This ILIR project was undertaken to make a start at predicting responses in environments where microwaves are present.

Others have shown the feasibility of modeling RFR effects with simple models (Adair, Berglund, 1985,86,92). Until recently, model testing has been restricted to animal data however some human physiological and subjective data are becoming available for validity testing from work at the J.B. Pierce Laboratory and Brooks Air Force Base. This project develops a simulation model using MATHLAB SIMULINK programming tools and compares the results to measurements by Adair (1999, 2001) made at Pierce and Brooks on human exposures to low level of microwave radiation.

METHODS

A relatively simple put widely accepted multi compartment lumped parameter model (Gagge, 1971, 1986) was used for the adaptation. It is a simplification of other more complicated models and considers the person to be represented by two thermal compartments (nodes), one representing the skin and the other the body core. This is a reasonable model for neutral and warm environments with low to medium activity because blood flow distributes heat and temperature rather uniformly in each of these compartments. It is also a good model for comparison to the available experimental human data which is now limited to core and skin temperatures, local sweat and skin blood flow rates and maybe how they feel.

In this model all metabolism occurs in the core, the core looses heat passively by conduction to the skin and by respiration and actively by regulating blood flow to the skin compartment. The metabolism while behaviorally dependent is automatically increased to a limited extent with hypothermia by regulating muscle tension and shivering. In turn the skin receives the heat from the core and passively transfers it to the environment. When that is insufficient, the body can initiate regulated sweating and the powerful cooling effects of evaporation. Radio frequency radiation can pass through normal dry clothing and be absorbed by both the skin and core compartments. Absorption in tissue generally takes place in the first wavelength of penetration. At microwave frequencies of 10 GHz and higher the radiation's wavelength in air is short [λ=c/f=(3x10^10)/(10x10^9)=3 cm$\approx$1inch] and the RF energy is absorbed in the skin or close to it. Frequencies of 300 MHz and less have a wavelength in air of 1m or more and for these frequencies the energy can be assumed to be absorbed by the core.

For this project a systems approach to model development was done using Simulink by MathWorks. Simulink (Dabney, 2001) is a computer language or modeling tool that facilitates the building of computer models using graphical block diagram notation and connectors to simulate dynamic systems. The programs visually look much like electrical circuit diagrams (Appendix A). The block diagram-connector notation reduces the time to prepare and test code, facilitates debugging, documentation and visualization of results. It also reduces the specific computer coding skills needed by the modeler/programmer. Further, the block diagram method also makes it easier to explain the code to others and for other to contribute to a system's development.

SIMULATION MODEL WITH MICROWAVE ENERGY ABSORPTION

After the 2 node Model was running in Simulink and verified, the microwave absorption features were added. The absorbed microwave energy (AMicro) was modeled in terms of incident power density (IPD, Watts/m2), the projected area (Ap) of the body that intercepts the radiation and the energy fractions absorbed (α), transmitted (τ) and reflected (ρ) by skin and core compartments as appropriate.

$$AMicro = \alpha * Ap * IPD$$

The method has also predicted reasonable results for squirrel monkeys (Berglund, 1983). Absorption is wavelength dependent so longer wave RFR will penetrate further before being absorbed. The model to date has been developed for beam mono-frequency microwave radiation. For beam radiation, the skin compartment is further divided into radiated and non-radiated compartments. A schematic representation of the model is shown in Figure 1.

THERMAL SENSATION

Important aspects of a human's responses to the environment are their thermal comfort sensations. These emanate from thermal and other sensors in the body and are generally proportional to physiological strains. The sensations can be a motivator for behavioral protective actions. The simulation model uses deviations in the predicted

skin and core temperature and skin moisture to predict the simulated person's thermal sensation and discomfort



Figure 1.Three-compartment thermo-physiological model for microwave beam radiation.

RESULTS

MODEL TESTING

The Simulink simulation model was tested and exercised sufficiently to discover and correct bugs and instability conditions. It was then compared to human RFR response data measured by Dr Adair and colleagues from human experiments conducted at the J.B. Pierce Laboratory and at Brooks Air Force Base. Such response data included core and skin temperatures, skin blood flow, sweat rates and subjective responses measured under repeatable conditions and are very scarce.

To date the model has been compared to the responses of volunteers wearing shorts in uniform environments of 28 and 31°C experiencing beam radiation to the back while seated on a stool. The measurements where done in absorbing non-reflective chambers to eliminate diffuse RFR.

100 MHz

Figure 2 compares the predicted (Tc) to the measured core temperatures (Tc exp) (mean of 7 subjects) for 100MHz radiation with an intensity of 8 mw/cm^2 (80 w/m^2) to the back in a 31C still air environment. The simulation assumed in this case that the core absorbed all of the radiation incident on the back. Figure 2 also shows the simulated skin temperatures for radiated (Tskrfr) and non-radiated (Tsk) skin. Comparable measured skin temperatures data were not available.



Figure 2. Thermal responses to 100 MHZ RFR in a 31C environment.

The simulated and measured sweat rates on the chest and back are compared in Figure 3. The shape of the responses for both simulated and measured conditions are similar except at the 30 minute mark. Encouraging is that the measured chest and back sweating rates are the same, indicating an absence of a radiation affects on the skin of the (radiated) back as assumed by the model for this frequency.

.



Figure 3. Local sweat rates in a 31C environment with 100 MHz RFR

Figure 4 compares the measured and simulated skin blood flows of the same condition. The measured local skin blood flows have the same response shape but are much higher than predicted. In this case it is suspected that laser Doppler blood measurements are too high as the reported values(chest exp, back rfr exp) appear excessive for the sedentary comfort condition.



Figure 4. Local skin blood flow in a 31C environment with 100 MHz RFR.

The simulated skin moisture levels for the radiated (rfr) and non-radiated areas of the skin are displayed in Figure 5. Skin moisture is expressed here in terms of skin wettedness (wet) which is the fraction of skin covered with water to account for the evaporation rate. Measured skin wettedness levels were not available for comparison.



Figure 5. Predicted skin moisture in a 31C environment with 100 MHz RFR.

The simulated whole body thermal sensation (Tsens) and discomfort responses for the simulated person are given in Figure 6. The simulation indicates the RFR exposed person will feel warmer with increased thermal discomfort.



Figure 6. Comfort responses in a 31C environment with 100 MHz RFR.

450MHz

The following comparisons are for exposures to 450 MHz RFR in 28 and 31 C environments. The volunteer sat on a stool in shorts with his or her back facing the antenna or wave-guide. The climate controlled chamber had RFR absorbing non-reflective surfaces.

Figure 7 thru 9 are for the 28 C environment where the experimental values are the mean of 7 subjects. The experimental skin and core temperatures are compared to those predicted by the simulation model in Figure 7. The skin temperatures agree well at this 24 mw/cm^2 (240 w/m^2) level as do the core temperatures, though the measured core temperature (Tc exp) after the radiation is unchanged and cooler than that predicted by the simulation model. The deviations between simulated and measured skin temperatures are always less than 0.5 C. The simulation was made assuming all the RFR energy was absorbed in the core (ask=0). This is an oversimplification for 450MHz RFR as discussed in the Background section, but the overall agreement was better than assuming it was all absorbed by the skin (ask=1).



Figure 7. Skin and core temperatures in a 28C environment with 450 MHz RFR.

The sweat rates at the same conditions are compared in Figure 8. The agreement is fairly good expect for the back measurements(sweat rfr exp) measured before radiation started.



Figure 8. Local sweat rates in a 28C environment with 450 MHz RFR.

The mean whole body thermal sensations and discomfort judgments of the seven subjects are compared to predictions in Figure 9 for the 450 MHz RFR, 28C conditions. The agreement for discomfort is fairly good. The simulation over- predicted the warmth sensation felt by these subjects at the end of the RFR exposure, further indicating that



Figure 9. Comparison of comfort sensations with 450 MHz in 28C air.

less RFR was absorbed by the core than the model assumed for 450MHz.

The comfort responses of a single subject in a 31 C environment with 450 MHz RFR at 24 mw/cm^2 are compared to simulated predictions in Figure 10. The agreement is fairly good and indicates a person may be able to learn to feel the RFR heat sufficiently to behaviorally self protect from further exposure.



Figure 10. Comfort sensations from one subject receiving 450 MHz RFR in 31C air compared to predicted sensations.

CONCLUSIONS

This modeling report is a first attempt approach resulting from an ILIR project. The project assembled and tested a computer simulation model that predicts the thermal physiological and sensation responses of humans exposed to radio frequency radiation. The simulation model is operational. It rationally predicts core temperature, thermal sensation and discomfort and regional skin temperatures, skin blood flows, sweat rates, and skin wettedness levels for radiated and non-radiated skin areas of an exposure. Model prediction results were compared to recent human test data measured by Dr. Adair at Brooks Air Force Base and J.B Pierce Laboratory. The test data radiation was 100 and 450 MHz at intensities of 8 and 24 mw/cm^2 in environments of 28 and 31C.

The comparisons indicate that the human thermal response to 100 MHz beam radiation can be simulated with the assumption that all the RFR is absorbed by the body's core. This model assumption also worked fairly well for 450 MHz comparisons. At higher frequencies (>10 GHz) the model assumes RFR adsorption is confined to the skin area. Intermediate frequencies between 300 MHz and 10 GHz are assumed by the model to have adsorption in both core and skin tissues in relation to the calculated penetration depth for the frequency. The model's biophysics procedures for intermediate frequencies are uncompleted at this date.

RECOMMENDATIONS

It is recommended that the model evolution continue with comparison testing at frequencies higher than 450 MHz as data is found to be available. RFR is an increasing present energy component of the human environment. And human simulation models are an effective and expedient tool in planning activities where RFR may be present. Further it is recommended that protective clothing and other evasive action capabilities for the simulation model be encouraged and added.

REFERENCES

1. Adair, E. and Berglund, L., 1985. Comfort Heating with Microwaves: An Idea Whose Time May Have Come. *CLIMA 2000*,August,Copenhagen.

2. Adair, E. and Berglund, L., 1986a. On the Thermoregulatory Consequences of NMR Imaging. *Magnetic Resonance Imaging,* Vol. 4:321-333.

3. Adair, E. and Berglund, L., 1986b. Predicted Thermoregulatory Responses During Whole-Body MR Imaging. *Proceedings of Fifth Annual Society of Magnetic Resonance in Medicine*, August, pp.14-22.

4. Adair, E. and Berglund, L., 1992. Predicted Thermoregulatory and Comfort Consequences of Whole Body Magnetic Resonance Imaging. *Annals of the New York Academy of Sciences*, Vol. 649: 188-200, New York.

5. Adair, E., Kelleher, S., Berglund, L and Mack, G., 1999. Physiological and Perceptual Responses of Human Volunteers During Whole-Body RF Exposure at 450 Mhz. *Electricity and Magnetism in Biology and Medicine,* Edited by Bersani, Kluwer Academic/Plenum.

6. Adair, E, 2001. Data from Dr. Adair at Brooks Air Force Base by personal communication.

7. Berglund, L., 1983. Characterizing the Thermal Environment. In: *Microwaves and Thermoregulation*, Academic Press.

8. Dabney, J.B. and T.L.Harman. Mastering SIMULINK 4. Prentice Hall, 2001.

9. Gagge,A.P., Stolwijk, J.A.J. and Nishi, Y., 1971. An effective temperature scale based on a simple model of human regulator response. *ASHRAE Transactions* 77:247.

10. Gagge, A. P., Fobelets, A., and Berglund, L., L., 1986. A Standard Predictive Index of Human Response. *ASHRAE Transactions*, Vol. 92(2).

Appendix A

The simulation model in Simulink

November 8, 2001




1
Tsk
Tsk Ta1
1
Ta
Ta MRT1
7
MRT
Pa
Tdp
2
Pa
2
Rm
Rm
Rmnet w/m^2
WE
WE1
Met1
3
Rmnet
4
met
met
V
Clo
Clostill
Rpcl
Hc
5
V
8
Clo
9
Clostill
10
Rpcl
6
Hc
12
ApRFR/Adu1
projected area receiving RFR
to total skin area
.3
ApRFR/Adu
ApRFR/Adu
RFR mw/sqcm
Skin RFR absorptivity
RFRcore w/(m^2)
RFRskin w/(m^2)
RfrEquivMet.
11
RFRcore
13
RFRskin
14
RFRequivMet
24
RFR mw/sqcm
Switch
Ground
Ramp
1
skin absorption

Feedback for Ta=MRT simulations




0.0
WE
womenMet.mat
1
WE1
Time varying work efficiency WE
1
met
womenMet.mat
2
Met1
Time varying Met input file

Assume striking RFR not absorbed by skin is absorbed by core





Thermodynamic work efficiency

Rmnet = Rm-work
but WE = work/Rm
so Rmnet = Rm-WE*Rm
or Rmnet = Rm*(1-WE)


Time varying Ta input file
womenTa.mat
1
Ta1
Ta
28
Ta2
Tsk
Ta1
1
Tsk
For Ta=Tsk simulations


Clock
<=
Relational
Operator
10
Start Ta=Tskn control
1
<
2
Tsk
×
+
+
1
Ta1
1
Ta2
×


Humidity input
10
Tdpt
womenTdp.mat
Time varying Tdp
input file
f(u)
Pa
2
Tdp
torr mmhg
0
Pa1
1
Pa


.1
clo
2
Clo
.7
clostill
3
Clostill
Vapor Resistance
.155/(.45*2.2)
4
Rpcl


1
met
.05
V m/s
2.9
CHCVmin
met
V m/s
Hcmin
Hc1
5
Hc
1
V


1
met
Hc due to
body motion
5.66*u^.39
CHCA
.85
rest
u <0
compare CHCA
CHCA or 0
u >0
compare CHCVf
CHCVf or 0
w/(m^2)
1
Hc1
m/s
2
V m/s
8.6*u^.53
CHCV
u >0
compare CHCV
CHCV or 0
u <0
compare CHCV1
3
Hcmin
CHCVmin or 0


1
Ta
34
0.0014
Cress
×
1
Cres
3
Rm
2
Pa
44
Psresg
0.0023
Eress
×
2
Eres


1
Rmnet
2
RFRcore
3
Res
4
Hfc-sk
5
Hfc-skRFR
6
alpha
7
alphaRFR
Rmnet
RFRcore
Res
Hfc-sk
Hfc-skRFR
ARFR/Adu
alpha
alphaRFR
Tc
dTc
CrbalanceSub
1
Tc
Tc
dTc
HFc-sk
HFc-skRFR
alpha
alphaRFR
Dry
Esk
DryRFR
EskRFR
RFRskin
ARFR/Adu
Tsk
TskRFR
Tskave
Tmcntrlave
dTmcntrlav C/min
SkbalanceSub
3
Tsk
4
TskRFR
2
dTmbave
9
Dry
8
Esk
10
DryRFR
11
EskRFR
12
ARFR/Adu
13
RFRskin


1
Rmnet
2
RFRcore
3
Res
Adu
1.8
DTc
1/60
convert to min?
C/min
2
dTc
T
z-1
1
Tc
36.9
Tci
4
Hfc-sk
5
Hfc-skRFR
6
ARFR/Adu
(1-u)
7
alpha
8
alphaRFR
AlphaAve
1/(.97*(1-u)*70.)
TCcrn


1
Tc
2
dTc
3
HFc-sk
7
Dry
8
Esk
5
alpha
11
RFRskin
4
HFc-skRFR
9
DryRFR
10
EskRFR
6
alphaRFR
12
ARFR/Adu
Normally clothed skin
Adu
1.8
dTsk
1/60
convert to min
dTsk C/min
34.
Tski
T
z-1
Tsk
1
Tsk
dTsk,dTskRFR,dTskav,dTmb
1/(.97*u*70.)
Tcskn
Skin under RFR
Adu1
1.8
dTskRFR
1/60
convert to min1
dTskRFR
34.69
TskRFRi
TsRFR
2
TskRFR
(1 - u)
3
Tskave
1/(.97*u*70.)
TcskRFR
.9
.1
4
Tmcntrlave
5
dTmcntrlav C/min
.9
.1


3
Tc
4
Tsk
1
Pa
8
hc
2
Ta
9
MRT
10
clo
11
clostill
12
Rpcl
5
TskRFR
13
ARFR/Adu
Pa
Wet
Hc
Tsk
Ta
MRT
clo
clostill
Rpcl
TskRFR
WetRFR
Esk
Ediff1
Dry
Emax
EskRFR
EmaxRFR
EdiffRFR
DryRFR
6
Esk
6
met
7
Dry
7
V
9
EskRFR
8
DryRFR
Tc
Tsk
met
Emax
Ediff
V
Tskrfr
EmaxRFR
EdiffRFR
ARFR/Adu
Esk
EskRFR
HFc-sk
SKBFRFR
Rm
RegswRFR
wet
TTmbcnt
Regsw1
wetRFR
SKBF1
alpha
alphaRFR
HFc-skrfr
wetave
dripave
Eskave
Regswave
Tmbcnt
2
HFc-sk
19
SkbfRFR
1
Rm
21
RegswRFR
13
wet
12
TTmbcnt
20
Regsw1
14
wetRFR
18
Skbf
4
Alpha
5
AlphRFR
3
HFc - skRFR
15
wetave
16
dripave
17
Eskave1
22
Regswave
11
Tmbcnt
10
ARFR/Adu1


1
Pa
2
Wet
3
Hc
4
Tsk
f(u)
Psk
9
Rpcl
6
MRT
5
Ta
7
clo
8
clostill
11
WetRFR
f(u)
PskRFR
10
TskRFR
Pa
wet2
Hc
Rpcl
Psk
Facl
Esk
Ediff2
Emax
MRT
Tsk
Hc
Ta
clo
clostill
Facl
Rtcl
To
hr
Rtcl
Tsk
To
Dry
PaRFR
RpclRFR
hcRFR
wetRFR
PskRFR
FaclRFR
EskRFR
EdiffRFR
EmaxRFR
HcRFR
TskRFR1
To
hr
cloRFR
cloRFRstill
FaclRFR1
DryRFR w/(m^2)
1
Esk
2
Ediff1
4
Emax
3
Dry
5
EskRFR
7
EdiffRFR
6
EmaxRFR
8
DryRFR


2
Tsk
3
To
+
−
Tsk-To
1
Rtcl
×
÷
1
Dry


2
wet2
1
Pa
3
Hc
4
Rpcl
5
Psk
6
Facl
Pa
Hc
Rpcl
Psk
Facl
Emax
wet
Emax
Esk
Ediff
1
Esk
2
Ediff2
3
Emax


1
Pa
4
Psk
He
2
Hc
5
Facl
2.2
Lewis Relation
1
u
3
Rpcl
1
Emax


1
wet
.06*(1-u)
Fcn
2
Ediff
Esk
1
Esk
Edif
2
Emax
Esw


4
wetRFR
6
FaclRFR
3
hcRFR
5
PskRFR
2
RpclRFR
1
PaRFR
FaclRFR
hcRFR
PskRFR
EmaxRFR
RpclRFR
PaRFR
wetRFR
EskRFR
EmaxRFR
EdiffRFR
1
EskRFR
2
EdiffRFR
3
EmaxRFR

evaporation under clothing

?????? Also check on wetc




1
wetRFR
.06*(1-u)
2
EmaxRFR
×
×
+
+
2
EdiffRFR
1
EskRFR
EswRFR


5
clo
clo
Hc
Facl
Hr
Rtcl
2
Rtcl
6
clostill
.2
1+u
1
Facl
1
MRT
3
Hc
4
Ta
2
Tsk
MRT
Hr w/(m^2 C)
Tsk
HrSubsys
MRT
Hc
Ta
Hr
To
3
To
4
hr


2
Hc
4
Hr
3
Facl
Product
1
u
1
Rtcl
1
clo
.155
Gain

Estimate of linear radiation heat transfer coefficient
hr=4*.725*(5.67E-08)*((Tsk+MRT)/2+273)^3




1
MRT
4
Hr
2
Hc
3
Ta
1
To


2
TskRFR1
3
To
+_
×
÷
2
DryRFR w/(m^2)
Should use cloc for still air
6
cloRFRstill
.2
1+u
1
FaclRFR1
5
cloRFR
1
HcRFR
4
hr
Facl
clo
Hc
Hr
RtclRFR


3
Hc
4
Hr
1
Facl
Product
1
u
1
RtclRFR
2
clo
.155
Gain


1
Tc
2
Tsk
7
Tskrfr
3
met
4
Emax
5
Ediff
6
V
8
EmaxRFR
9
EdiffRFR
10
ARFR/Adu
11
Esk
12
EskRFR
Tsk
Tc
met
Emax
Ediff
V
TskRFR
Emaxrfr
Ediffc
Arfr/Adu
Esk
Eskrfr
SKBF
Rm
TTmbcnt
Tmbcnt
SKBFrfr
alpharfr
Regswrfr
wetrfr
driprfr
alpha
Regsw
wet
drip
Shiver/met
wetave
dripave
Eskave1
Rewswave
Skbfave
controlSubsystem
9
SKBF1
3
Rm
6
TTmbcnt
17
Tmbcnt
11
alphaRFR
4
RegswRFR
8
wetRFR
10
alpha
7
Regsw1
5
wet
13
wetave
14
dripave
15
Eskave
16
Regswave
Tc
Tsk
skbf
HFc-sk
core/skinSubsys
1
HFc-sk
Tc
Tskrfr
skbfrfr
HFc-skrfr
Core/RFRskinSubsys
12
HFc-skrfr
SKBFRFR
2



Core to skin heat transfer for area under air cooled clothing


nonradiated skin
areas under rfr beam
SignalSub
coldsk
warmsk
coldb
warmb
coldcr
warmcr
TTmbcnt
AlphaControl1
Tmbcnt
TskRFR
Tsk
Tc
ARFR/Adu
SignalSub1
coldskrfr
warmskrfr
coldbrfr
Tmbrfr
warmbrfr
Tskrfr
Tc
Alphacontol
TskRFR
7
Tsk
1
2
Tc
3
TTmbcnt
4
Tmbcnt
ActiveConrolSubsystem
coldsk
warmcr
Rmi
warmsk
warmb
coldcr7
Emax
Ediff
V5
SKBF
alpha
Regsw3
wet4
drip5
Rm
shiver/met
3
met
4
Emax
5
Ediff
6
V
10
Arfr/Adu
11
Esk
12
Eskrfr
10
alpha
11
Regsw
12
wet
13
drip
2
Rm
14
Shiver/met
1
SKBF
8
Emaxrfr
9
Ediffc
ActiveConrolSubsystemac
warmcr
warmskrfr
warmbrfr
Emaxrfr
Ediffrfr
coldskrfr
SKbfrfr
alpharfr
Regswrfr
wetrfr
driprfr
5
SKBFrfr
6
alpharfr
7
Regswrfr
8
wetrfr
9
driprfr
driprfr
wet
wetrfr
drip
Arfr/Adu
Esk
Eskrfr
Regsw
Regswrfr
Skbf
Skbfc
wetave
dripave
Eskave
Regswave
Skbfave
15
wetave
16
dripave
17
Eskave1
18
Rewswave
19
Skbfave


1
coldsk
2
warmcr
5
warmb
4
warmsk
7
Emax
8
Ediff
9
V5
warmcr
coldsk2
warmb
warmsk1
Emax1
Ediff1
V1
SKBF
alpha
Regsw1
wet1
drip1
NormalActivePhysiSub
1
SKBF
2
alpha
3
Regsw3
4
wet4
5
drip5
3
Rmi
6
coldcr7
Rmi
coldsk
coldcr
Rm
Shiver/met
ShiverSubm
6
Rm
7
shiver/met


0
0
1
warmcr
2
coldsk2
warmcr SKBF1
coldsk alpha1
SKBFSub
1
SKBF
2
alpha
0
0
0
4
warmsk1
3
warmb
5
Emax1
6
Ediff1
7
V1
warmsk
warmb
Emax
Ediff
V
Regsw
wet
drip
RegswSub
3
Regsw1
4
wet1
5
drip1
0


check if Regsw>667 g/(m^2*h)
increase sweat limit to 3000 g/(hm^2) July 6,01
1
warmsk
exp(u/10.7)
NadelSkinTerm
2
warmb
170
CSW
667
Regswmax
g/(m^2*h)
<=
==
0
true
true2
g/(h*m^2)
g/(m*m^2)
1/60
1
Regsw
.68
hfgsweat
w/(m^2)
g/(h*m^2)
4
Ediff
3
Emax
wet
1
wmax
2
wet
drip
0
>=
1/.68
g/(h*m^2)
1/hfgsweat
5
V
.38/u^.29
wcrit
Berglund&Gonzalez
JAP 42(5):767-772,1
g/(m*m^2)
1/60
3
drip


1
warmcr
6.3
SKBFn
50
Cdil
DiLate
2
coldsk
.5
Cstrt
Stric
1.+u
Fcn
SKBF
check if SKBF<1
1
SKBFmin
L/(m^2*h)
>=
<
1
true3
true5
check if SKBF>200
200
SKBFmax
L/(m^2*h)
<=
<
1
true
true2
1
SKBF1
.04177+.74518/(u+.585417)
alpha
2
alpha1


2
coldsk
3
coldcr
×
19.4
1/58.2
2
Shiver/met
+
+
1
Rm
1
Rmi
58.2


1
warmcr
2
warmskrfr
3
warmbrfr
4
Emaxrfr
5
Ediffrfr
6
coldskrfr
warmcr
warmskrfr
warmbrfr
Emaxrfr
Ediffrfr
coldskrfr
Regswrfr
wetrfr
driprfr
SKBFrfr
alpharfr
3
Regswrfr
4
wetrfr
5
driprfr
1
SKbfrfr
2
alpharfr
AcActivePhysiSubm

SubSystems for rfr beam






For skin under rfr beam
check if Regsw>667 g/(hm^2)
increase sweat limit to 3000 g/(hm^2)
1
warmskrfr
exp(u/10.7)
NadelSkinTerm
2
warmbrfr
170
3000
Regswmax
g/(m^2*h)
<=
==
0
true
true2
g/(h*m^2)
1/60
g/(m*m^2)
1
Regswrfr
0
Display
.68
hfgsweat
0
Display1
4
Ediffrfr
3
Emaxrfr
w/(m^2)
g/(h*m^2)
wet
1
wmax
<=
==
0
2
wetrfrc
drip
0
>=
1/.68
1/hfgsweat
g/(h*m^2)
1/60
g/(m*m^2)
3
driprfr


check if SKBF<1
check if SKBF>200
6.3
SKBFn
1
warmcr
50
Cdil
DiLate
2
coldskac
.5
Cstrt
Stric
1.+u
Fcn
SKBF
1
SKBFmin
L/(m^2*h)
>=
<
1
true3
true5
200
SKBFmax
L/(m^2*h)
<=
<
1
true
true2
1
SKBFrfr
0
Display
0
warmcr1
0
coldskrfr
.04177+.74518/(u+.585417)
alpha
2
alpharfr


2
Tsk
Tsk
<=
-1
33.7
TTsk
SKsig
1
<
.1
AlphaControl
Tmbcnt
1
coldsk
2
warmsk
(1-u)
TTmbcnt
3
coldb
0
4
warmb
3
Tc
7
TTmbcnt
36.8
TTcr1
Check control equations against Gagge 2NM???!!!
5
coldcr
6
warmcr
1
TskRFR
TskRFR
4
ARFR/Adu
(1-u)
8
AlphaControl1
9
Tmbcnt



Physiological Control signals for areas under rfr beam


2
wet
3
wetrfr
4
drip
5
Arfr/Adu
(1-u)
1
driprfr
6
Esk
7
Eskrfr
8
Regsw
9
Regswrfr
10
Skbf
11
Skbfc
1
wetave
2
dripave
3
Eskave
4
Regswave
5
Skbfave


1
Tc
2
Tsk
Tc-Tsk
5.28
Cmin
3
skbf
1.163
CB
×
1
HFc-sk


17
Eres
11
Eskave
10
dripave
16
Regswave
Eres
Eskave
dripave
Regswave
lost water L
RegswaveL/h
water loss L/h
water loss system
1
Tc
2
Tsk
3
TskRFR
Tc
Tsk1
TskRF1
Tskave1
water loss
RegswL/h7
7
wet
8
wetRFR
wet8
wetrfr
wetave1
9
wetave
4
Tmb
5
TTmb
6
dTmbave
wetave
Tmb
TTmb
dTmbave
Disc
Tsens
trTsens1
Disc
Tsens
trTsens
Tmb
dTmbave
12
Skbfn
13
SkbfRFR
14
Regswn
15
RegswRFR
Skbf1
Skbfrfr
Regswn1
Regswrf
18
Met
19
RFRequivMet
met
RFRequivMe
output


from 2nm 1/13/84
4.987u-.17
1
wetave
4.9879*u -.17
1
Disc
also based on Gagge 2nm ASHRAE 86
Disc=4u/.8-.17
disc,Tsens,trTsens
2
Tmb
3
TTmb
7.883*u-.8542
<=
×
+
+
2
Tsens
from 2nm 1/13/84
7.883u-.854
Tsens Limited to<=5
5
0
==
×
Tmb,dTmb
transient weighting??
1
+
+
3
trTsens1
Transient Tsens
also based on Gagge 2nm ASHRAE 86
Disc=4u/.8-.17
4
dTmbave
7.883*u
<=
×
+
+
from 2nm 1/13/84
7.883u-.854
Tsens Limited to<=5
5
0
==
×


1
Tc
2
Tsk1
3
TskRF1
4
Tskave1
Tc1
Tsk
TskRF
Tskave
SkBF1
Regsw1
Skbf1
15
Skbf
16
Skbfrfr
SkBF
SKbfrfr
17
Regswn1
1.8*60/1000
L/h
Regsw
18
Regswrf
1.8*60/1000
Regswrfr
5
water loss
6
RegswL/h7
Scope6
Waterlos L
Regswave L/h
Regsw2 2/(min m^2)
7
wet8
wet1
8
wetrfr
wetrfr1
9
wetave1
wetave
wet
10
Disc
Disc1
11
Tsens
disc1
Tsens1
12
trTsens
trTens
sweatave,sweatRF,sweat L/h
13
Tmb
Tmbave
14
dTmbave
Tmb dTmb
dTmbave C/min
19
met
20
RFRequivMet
met,totalmet,RFRequivmet


1
Eres
2
Eskave
1/(.68*60)
1.8*60
3
water loss L/h
g/(min*m^2)
Cumulative
water loss L
L
3
dripave
T
z-1
1.8/1000*u
1
lost water L
0
H2Oi
x_0
4
Regswave
60*1.8/1000*u
Regsw L /h
2
RegswaveL/h

Appendix B

Human response data used in comparison testing

PHYSIOLOGICAL AND PERCEPTUAL RESPONSES OF HUMAN VOLUNTEERS DURING WHOLE-BODY RF EXPOSURE AT 450 MHz

Eleanor R. Adair,[1] Sharon A. Kelleher,[2] Larry G. Berglund,[3] and Gary W. Mack[2]

[1]Armstrong Laboratory, Brooks Air Force Base, TX
[2]John B. Pierce Laboratory, New Haven, CT
[3]Tohoku University, Aoba-Ku, Sendai, Japan

INTRODUCTION

The razionale behind all investigations of radio frequency (RF) bioeffects, whether *in vivo or in vitro,* ultimately concerns the effects of such exposure on human beings. Voluminous animal bioeffects data have been collected over the last 40-50 years. However, controlled laboratory investigations of human responses to such fields are meager and tend to be limited to sensory endpoints. We have initiated a series of studies to obtain accurate knowledge of human thermoregulatory efficiency in the RF environment; these data are designed to provide generalizable functional relationships that can serve as the basis for human safety guidelines. The functions will also be invaluable to the refinement of computer models designed to predict human thermoregulatory responses in the presence of RF energy and aid the extrapolation of animal data to the human condition. As adjuncts to the physiological data, we have also developed a set of criteria by which R.F-exposed humans may rate their perceptual impressions of their thermal environment and their physiological responses. The perceptual data are featured in this report.

MIETHODS

We have developed techniques and protocols to assess responses of heat production and heat loss in human volunteers exposed dorsally to RF energy at 450 MHz. These physiological measures included deep body temperature (esophageal), 6 skin temperatures (upper and lower back, chest, forearm, thigh, and forehead), metabolic heat production from O_2 consumption and CO_2 production, skin blood flow (back), and local sweating rate (back and chest). We also obtained periodic judgments of thermal sensation and thermal comfort, perceived skin wettedness and sweating, thermal preference and thermal acceptability. Seven adult volunteers served as subjects, 4 females and 3 males, aged 21 to 57 years. Each subject was tested nine times using a protocol that involved 45-min whole body exposures to 450 MHz CW R-F energy or sham exposure (no RF present).

During the test, the fully-instrumented subject sat in the far field of a dipole antenna (mounted in a corner reflector) inside an anechoic chamber. The subject's compartment was maintained at one of three ambient temperatures (T_a), 24, 28 or 31 °C (cool, neutral, or warm). The subject was in continuous video and audio contact with the experimenters outside the chamber. Two power densities [peak PD = 18 and 24 mW/cm^2; peak specific absorption rate (SAR) = 0.032 (W/kg)/(mW/cm^2)] were tested in each of the three T_a, plus T_a controls (no R.F). The protocol for each test session was the same and comprised three temporal segments: a 30-min equilibration to the T_a, a 45-min RF (or sham) exposure, and a 10-min re-equilibration. At minutes 25, 45, 65, and 80, the subject was asked to rate thermal comfort, thermal sensation, perceived skin wettedness, perceived sweating, T_a preference, and T_a acceptability, using specific category scales.

The subject was asked "How do you feel at this moment?" and rated thermal comfort on a scale from comfortable (0) to intolerable (4), and thermal sensation on a scale from very hot (4) to neutral (0) to very cold (-4). Next the subject was asked to rate skin wettedness on a scale from soaking wet (6) to very dry (0) and perceived sweating on a scale from maximum (5) to none (0). Finally, the subject was asked for thermal preference (cooler = -1, no change = 0, warmer = 1), and whether the environment was thermally acceptable (yes or no).

Electricity and Magnetism in Biology and Medicine
Edited by Bersani, Kluwer Academic/Plenum Publishers, 1999

RESULTS

Mean minute-to-minute values of all measured variables were calculated across the 7 subjects for each test condition. Figure 1 shows representative physiological data for the group of 7 subjects, exposed to RF energy in the thermoneutral environment of 28 °C. Open symbols code the data for a power density of 18 mW/cm^2, while closed symbols code the data for the higher power density, 24 mW/cm^2. Control (no RF) data are not included in the figure. The upper panel shows esophageal and selected skin temperatures, while the lower panel shows sweating rate from the chest and the back. The vertical lines indicate the end of the 30-min equilibration period, and the end of the 45-min RF exposure period. Some rise in skin temperatures, particularly on the back occurred during RF exposure, but sweating occurred on back and chest only during exposure to the higher power density. However, during RF exposure at both power densities, no change occurred in the deep body temperature, measured in the esophagus at the level of the health. During tests in the cool (T_a = 24 °C) environment, no subject exhibited sweating during RF exposure, skin temperature elevations were modest, and no change was measured in esophageal temperature. In the warm (T_a = 31 °C) environment, all subjects were sweating under the high power density, most under the lower power density; some skin temperatures fell during RF exposure due to skin cooling associated with the evaporation of sweat but still no significant rise in esophageal temperature occurred.



Figure 1. Group mean physiological responses for two power densities in the 28 °C environment. Body temperatures shown in top panel, local sweating rate in the bottom panel.



Figure 2. Local sweating rate (back and chest) and perceptual data for one subject exposed to 450 MHz CW RF energy at 24mW/cm^2 in the warm environment.

Perceptual data reflected the physiological state of the subjects. The upper panel of Figure 2 shows local sweating rate data for a single subject under the most thermally-stressful conditions: the higher power density in the warm environment. Although some sweating was evident during the initial 30-min equilibration period, sweating rate increased to significantly higher levels on both back and chest during RF exposure. During this time, judgments of thermal comfort deteriorated from near-comfortable to uncomfortable, thermal sensation rose from neutral to hot, perceived skin wettedness rose from dry to wet, and perceived sweating rose from none to 50% of maximum. All responses, both sweating and perceptual judgments trended toward their initial values when the RF was turned off.



Figure 3. Group mean judgments of thermal comfort (left) and thermal sensation (right), taken five minutes before the end of the 45min RF exposure period, as a function of the prevailing ambient temperature. Black bars indicate control (no RF) tests, dark gray bars indicate tests of the lower power density, and light gray bars indicate tests of the higher power density.



Figure 4. Group mean judgments of skin wettedness (A), perceived sweating (B), thermal preference (C), and thermal acceptability (D), taken five minutes before the end of the RF exposure, as a function of prevailing ambient temperature. Bars coded as in Figure 3.

Figure 3 shows group mean judgments of thermal comfort and thermal sensation just 5 minutes before the RF energy was turned off. Shown are control (sham) exposures in black bars, the low power density in dark gray bars, and the high power density in light gray bars for each test environment, 24, 28 and 31 °C. Only in the cool environment did RF exposure increase thermal comfort, and it did so by changing a cool sensation to a warmer one. In the neutral and warm environments. RF exposure decreased thermal comfort and increased the sensation of warming in proportion to the power density. Further analyses of these data indicated that the change in thermal comfort and thermal sensation, from the end of the equilibration period to the end of the RF exposure period, had little to do with the change in mean skin temperature that occurred, except in the thermoneutral environment. Thus, in the cool environment, skin temperature rose during RF exposure, but thermal comfort deteriorated and thermal sensation changed very little. In the warm environment, skin temperatures rose only slightly during RF exposure due to sweating, but discomfort increased sharply and the subjects reported that they felt much warmer. However, in the neutral environment, both thermal discomfort and the sensation of warming increased in proportion to the rise in mean skin temperature, which was in turn dependent on the power density of the exposure field.

Figure 4 shows mean judgments of skin wettedness, perceived sweating, thermal preference and thermal acceptability taken after 40 minutes of RF (or sham) exposure. Both perceived wettedness and perceived sweating increased in the presence of RF in all environments. The environment was judged thermally acceptable under all conditions EXCEPT during RF exposure at T_a = 31 °C. On the other hand, subjects wanted the environment warmer only in the 24 °C with no RF presents wanted no change in the 24 °C environment with 18 mW/cm^2 and the neutral environment with no RF present. Otherwise the subjects wanted their environment cooler. A comparison between the judgments of perceived sweating and actual sweat rate measurements at the two skin sites showed some discordance between the two. Subjects did not sweat at all in the cool environment and, in the neutral environment (T, = 28 °C), sweating was measured only when the 24 mW/cm^2 field was present. In some of these cases, subjects judged that they were sweating when they were not. On the other hand, when subjects were actually sweating, such as in the warm environment when the RF field was present, their perceptions were reasonably accurate. Thermal physiologists have traditionally linked thermal discomfort with skin wettedness[1]. A comparison between the thermal comfort data in Figure 3 and the skin wettedness data in panel A of Figure 4, in fact, confirm this strong association. In this context it is important to remember that a judgment of "0" on the thermal comfort scale indicates maximal comfort, while judgments of " 1 ", "2", etc. indicate greater and greater discomfort.

SUMMARY AND CONCLUSIONS

The study described here is the first of a planned series in which human volunteers undergo exposure of the whole body to controlled RF fields in highly controlled thermal environments. At the highest peak power density explored in the present study (24 mW/cm^2), the calculated whole-body SAR of 0.19 W/kg was well within the ANSI/IEEE C95.1-1992 guideline[2] for a "controlled environment" at 450 MHz, but was more than double the guideline for an "uncontrolled environment". In our experiments, we found that, even under ambient conditions (including RF exposure) that were often judged to be uncomfortable and thermally stressful, the internal body temperature of the subjects was regulated with precision by the mobilization of appropriate heat loss responses, principally sweating. Further, the subjects were generally aware of their altered thermal environment and their own physiological state. These perceptions could lead to effective evasive action, if necessary, to maintain thermal homeostasis.

REFERENCES

1. ASHRAE Fundamentals (1 993). Chapter 8. Physiological principles and thermal comfort. Atlanta, GA:American Society of Heating, Refrigerating, and Air-Conditioning Engineers, pp. 8.1 - 8.29
2. ANSI/IEEE C95.1 (1992). IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.. New York: Institute of Electrical and Electronics Engineers.


100 MHz CW Microwaves
esoph
ankle
Temperature (°C)
Group Mean N=7
31°C 8mW/cm²
chest
back
Local Sweat Rate (mg/min/cm²)
Time (minutes)


100 MHz CW Microwaves
Metabolic Heat Production (W/kg)
back
chest
thigh
Skin Blood Flow (AU)
Time (minutes)